

Package: freqtables (via r-universe)

August 15, 2024

Type Package
Title Make Quick Descriptive Tables for Categorical Variables
Description Quickly make tables of descriptive statistics (i.e., counts, percentages, confidence intervals) for categorical variables. This package is designed to work in a Tidyverse pipeline, and consideration has been given to get results from R to Microsoft Word ® with minimal pain.
Version 0.1.1
Maintainer Brad Cannell <brad.cannell@gmail.com>
URL <https://github.com/brad-cannell/freqtables>
BugReports <https://github.com/brad-cannell/freqtables/issues>
License MIT + file LICENSE
Encoding UTF-8
RoxygenNote 7.2.2
Imports dplyr, rlang, stringr
Suggests testthat (>= 2.1.0), knitr, rmarkdown
VignetteBuilder knitr
Depends R (>= 2.10)
LazyData true
Repository <https://brad-cannell.r-universe.dev>
RemoteUrl <https://github.com/brad-cannell/freqtables>
RemoteRef HEAD
RemoteSha e5ea40427654c0aeef79aa1d54a204638eb17e89

Contents

freq_format	2
freq_study	3
freq_table	4
freq_test	7
get_group_n	9

freq_format	<i>Format freq_table Output for Publication and Dissemination</i>
-------------	---

Description

The freq_format function is intended to make it quick and easy to format the output of the freq_table function for tables that may be used for publication. For example, a proportion and 95 could be formatted as "24.00 (21.00 - 27.00)."

Usage

```
freq_format(.data, recipe, name = NA, digits = NA)
```

Arguments

.data	A data frame of class "freq_table_one_way" or "freq_table_two_way".
recipe	A recipe used to create a new column from existing freq_table columns. The recipe must be in the form of a quoted string. It may contain any combination of column names, spaces, and characters. For example: "n (percent)" or "percent (lcl - ucl)".
name	An optional name to assign to the column created by the recipe. The default name is "formatted_stats"
digits	The number of decimal places to display.

Value

A tibble

Examples

```
library(dplyr)
library(freqtables)

data(mtcars)

# One-way frequency tables with defaults

mtcars %>%
  freq_table(am) %>%
  freq_format(
    recipe = "percent (lcl - ucl)",
    name = "percent_95",
    digits = 2
  ) %>%
  select(var, cat, percent_95)
#> # A tibble: 2 x 3
#>   var   cat  percent_95
```

```

#>   <chr> <chr> <chr>
#> 1 am    0    59.38 (40.94 - 75.50)
#> 2 am    1    40.62 (24.50 - 59.06)

# Two-way frequency tables with defaults

mtcars %>%
  freq_table(am, cyl) %>%
  freq_format(
    recipe = "percent_row (lcl_row - ucl_row)",
    name = "percent_95",
    digits = 2
  ) %>%
  select(1:4, percent_95)
#> # A tibble: 6 x 5
#>   row_var row_cat col_var col_cat percent_95
#>   <chr>   <chr>   <chr>   <chr>   <chr>
#> 1 am     0     cyl     4     15.79 (4.78 - 41.20)
#> 2 am     0     cyl     6     21.05 (7.58 - 46.44)
#> 3 am     0     cyl     8     63.16 (38.76 - 82.28)
#> 4 am     1     cyl     4     61.54 (32.30 - 84.29)
#> 5 am     1     cyl     6     23.08 (6.91 - 54.82)
#> 6 am     1     cyl     8     15.38 (3.43 - 48.18)

```

freq_study

Simulated study data.

Description

This is the code to create the study data - a simulated dataset that can be used to demonstrate how to use the 'freqtables' package.

Usage

```
freq_study
```

Format

A data frame with 100 rows and 6 variables:

id Participant's study identification number

age_group Participant's age at the time of enrollment categorized as "Younger than 30" or "30 and Older"

sex Biological sex of the participant assigned at birth, female/male

bmi_4cat Participant's bmi at date of enrollment categorized as "Underweight", "Normal", "Overweight", or "Obese"

exposure Participant was exposed to a hypothetical risk factor of interest, Yes/No

outcome Participant experienced a hypothetical outcome of interest, Yes/No

freq_table	<i>Estimate Counts, Percentages, and Confidence Intervals in dplyr Pipelines</i>
------------	--

Description

The `freq_table` function produces one-way and two-way frequency tables for categorical variables. In addition to frequencies, the `freq_table` function displays percentages, and the standard errors and confidence intervals of the percentages. For two-way tables only, `freq_table` also displays row (subgroup) percentages, standard errors, and confidence intervals.

`freq_table` is intended to be used in a `dplyr` pipeline.

All standard errors are calculated as some version of: $\sqrt{\text{proportion} * (1 - \text{proportion}) / (n - 1)}$

For one-way tables, the default 95 percent confidence intervals displayed are logit transformed confidence intervals equivalent to those used by Stata. Additionally, `freq_table` will return Wald ("linear") confidence intervals if the argument to `ci_type = "wald"`.

For two-way tables, `freq_table` returns logit transformed confidence intervals equivalent to those used by Stata.

Usage

```
freq_table(.data, ..., percent_ci = 95, ci_type = "logit", drop = FALSE)
```

Arguments

<code>.data</code>	A data frame. If it is already grouped (i.e., <code>class == "grouped_df"</code>) then <code>freq_table</code> will ungroup it to prevent unexpected results. For two-way tables, the count for each level of the variable in the first argument to <code>freq_table</code> will be the denominator for row percentages and their confidence intervals. Said another way, the goal of the analysis is to compare percentages of some characteristic across two or more groups of interest, then the variable in the first argument to <code>freq_table</code> should contain the groups of interest, and the variable in the second argument to <code>freq_table</code> should contain the characteristic of interest.
<code>...</code>	Categorical variables to be used in calculations. Currently, <code>freq_table</code> accepts one or two variables – not more. By default, if <code>...</code> includes a factor variable with a level (category) that is unobserved in the data, that level will still appear in the results with a count (n) equal to zero. This behavior can be changed using the <code>drop</code> parameter (see below). When <code>n = 0</code> , the confidence intervals will be NaN.
<code>percent_ci</code>	sets the level, as a percentage, for confidence intervals. The default is <code>percent_ci = 95</code> for 95 percentage value entered (e.g., 95) is converted to an alpha level as $1 - (\text{percent_ci} / 100)$. It is then converted to a two-sided probability as $(1 - \alpha / 2)$, which is used to calculate a critical value from Student's t distribution with $n - 1$ degrees of freedom.

ci_type	Selects the method used to estimate 95 percent confidence intervals. The default for one-way and two-way tables is logit transformed ("log"). For one-way tables only, ci_type can optionally calculate Wald ("linear") confidence intervals using the "wald" argument.
drop	If false (default) unobserved factor levels will be included in the returned frequency table with an n of 0. For example, if you have a factor variable, gender, but no males in your data then frequency table returned by freq_table(df, gender) would still contain a row for males with the variable n = 0. If drop is set to TRUE, then the resulting frequency table would not include a row for males at all.

Value

A tibble with class "freq_table_one_way" or "freq_table_two_way"

References

Agresti, A. (2012). Categorical Data Analysis (3rd ed.). Hoboken, NJ: Wiley.

[SAS confidence limits for proportions documentation](#)

[Stata confidence limits for proportions documentation](#)

Examples

```
library(dplyr)
library(freqtables)

data(mtcars)

# -----
# One-way frequency table with defaults
# - The default confidence intervals are logit transformed - matching the
#   method used by Stata
# -----
mtcars %>%
  freq_table(am)

# A tibble: 2 x 9
#   var   cat      n n_total percent    se t_crit   lcl   ucl
#   <chr> <chr> <int>  <int>   <dbl> <dbl>  <dbl> <dbl> <dbl>
# 1 am    0      19     32    59.4  8.82   2.04  40.9  75.5
# 2 am    1      13     32    40.6  8.82   2.04  24.5  59.1

# -----
# One-way frequency table with arbitrary confidence intervals
# - The default behavior of freq_table is to return 95% confidence
#   intervals (two-sided). However, this behavior can be adjusted to return
#   any alpha level. For example, to return 99% confidence intervals just
#   pass 99 to the percent_ci parameter of freq_table as demonstrated below.
# -----
mtcars %>%
```

```

freq_table(am, percent_ci = 99)

# A tibble: 2 x 9
#   var   cat      n n_total percent    se t_crit   lcl   ucl
#   <chr> <chr> <int>  <int>   <dbl> <dbl>  <dbl> <dbl> <dbl>
# 1 am    0      19     32    59.4  8.82   2.74  34.9  79.9
# 2 am    1      13     32    40.6  8.82   2.74  20.1  65.1

# -----
# One-way frequency table with Wald confidence intervals
# Optionally, the ci_type = "wald" argument can be used to calculate Wald
# confidence intervals that match those returned by SAS.
# -----
mtcars %>%
  freq_table(am, ci_type = "wald")

# A tibble: 2 x 9
#   var   cat      n n_total percent    se t_crit   lcl   ucl
#   <chr> <chr> <int>  <int>   <dbl> <dbl>  <dbl> <dbl> <dbl>
# 1 am    0      19     32    59.4  8.82   2.04  41.4  77.4
# 2 am    1      13     32    40.6  8.82   2.04  22.6  58.6

# -----
# One-way frequency table with drop = FALSE (default)
# -----
df <- data.frame(
  id = c(1, 2, 3, 4),
  gender = factor(
    # All females
    c(1, 1, 1, 1),
    levels = c(1, 2),
    labels = c("female", "male"))
)

df %>%
  freq_table(gender)

# A tibble: 2 x 9
#   var   cat      n n_total percent    se t_crit   lcl   ucl
#   <chr> <chr> <int>  <int>   <dbl> <dbl>  <dbl> <dbl> <dbl>
# 1 gender female     4      4    100     0   3.18   NaN   NaN
# 2 gender male      0      4     0     0   3.18   NaN   NaN

# -----
# One-way frequency table with drop = TRUE
# -----
df <- data.frame(
  id = factor(rep(1:3, each = 4)),
  period = factor(rep(1:4)),
  x = factor(c(0, 0, 0, 1, 0, 1, 1, 1, 0, 0, 1, 1))
)

```

```

)

# Now, suppose we want to drop period 3 & 4 from our analysis.
# By default, this will give us 0s for period 3 & 4, but we want to drop them.

df <- df %>%
  filter(period %in% c(1, 2))

df %>%
  freq_table(period)

# A tibble: 4 x 9
#   var   cat    n n_total percent    se t_crit    lcl    ucl
#   <chr> <chr> <int>   <int>   <dbl> <dbl> <dbl> <dbl> <dbl>
# 1 period 1     3     6     50  22.4  2.57  9.12  90.9
# 2 period 2     3     6     50  22.4  2.57  9.12  90.9
# 3 period 3     0     6     0  0    2.57 NaN   NaN
# 4 period 4     0     6     0  0    2.57 NaN   NaN

# But, we don't want period 3 & 4 in our frequency table at all. That's
# when we should change drop to TRUE.

df %>%
  freq_table(period, drop = TRUE)

# A tibble: 2 x 9
#   var   cat    n n_total percent    se t_crit    lcl    ucl
#   <chr> <chr> <int>   <int>   <dbl> <dbl> <dbl> <dbl> <dbl>
# 1 period 1     3     6     50  22.4  2.57  9.12  90.9
# 2 period 2     3     6     50  22.4  2.57  9.12  90.9

# -----
# Two-way frequency table with defaults
# Output truncated to fit the screen
# -----

mtcars %>%
  freq_table(am, cyl)

# A tibble: 6 x 17
#   row_var row_cat col_var col_cat    n n_row n_total percent_total se_total
#   <chr>   <chr>   <chr>   <chr>   <int> <int>   <int>           <dbl>   <dbl>
# 1 am     0      cyl     4         3   19    32           9.38     5.24
# 2 am     0      cyl     6         4   19    32          12.5     5.94
# 3 am     0      cyl     8        12   19    32          37.5     8.70
# 4 am     1      cyl     4         8   13    32           25     7.78
# 5 am     1      cyl     6         3   13    32           9.38     5.24
# 6 am     1      cyl     8         2   13    32           6.25     4.35

```

Description

The `freq_test` function is an S3 generic. It currently has methods for conducting hypothesis tests on one-way and two-way frequency tables. Further, it is made to work in a dplyr pipeline with the `freq_table` function.

For the `freq_table_two_way` class, the methods used are Pearson's chi-square test of independence Fisher's exact test. When cell counts are ≤ 5 , Fisher's Exact Test is considered more reliable.

Usage

```
freq_test(.data, ...)

## S3 method for class 'freq_table_one_way'
freq_test(.data, ...)

## S3 method for class 'freq_table_two_way'
freq_test(.data, ...)
```

Arguments

<code>.data</code>	A tibble of class <code>freq_table_one_way</code> or <code>freq_table_two_way</code> .
<code>...</code>	Other parameters to be passed on.
<code>method</code>	Options for this parameter control the method used to calculate p-values.

Value

A tibble.

Examples

```
library(dplyr)
library(freqtables)

data(mtcars)

# Test equality of proportions

mtcars %>%
  freq_table(am) %>%
  freq_test() %>%
  select(var:percent, p_chi2_pearson)

#> # A tibble: 2 x 6
#>   var   cat    n n_total percent p_chi2_pearson
#>   <chr> <dbl> <int>   <int>   <dbl>         <dbl>
#> 1   am     0    19      32    59.38      0.2888444
#> 2   am     1    13      32    40.62      0.2888444

# Chi-square test of independence

mtcars %>%
```



```

freq_table(am, vs) %>%
freq_test() %>%
select(row_var:n, percent_row, p_chi2_pearson)

#> # A tibble: 4 x 7
#>   row_var row_cat col_var col_cat     n percent_row p_chi2_pearson
#>   <chr>   <dbl>   <chr>   <dbl> <int>         <dbl>         <dbl>
#> 1     am     0     vs     0     12         63.16         0.3409429
#> 2     am     0     vs     1     7          36.84         0.3409429
#> 3     am     1     vs     0     6          46.15         0.3409429
#> 4     am     1     vs     1     7          53.85         0.3409429

```

get_group_n

*Formatted Group Sample Size for Tables***Description**

Given a tibble and a filter expression, `get_group_n` returns the group sample size formatted as "N = XXXX". Made to work in a dplyr pipeline, and used when creating tables for publications / reports.

Usage

```
get_group_n(.data, ...)
```

Arguments

`.data` A data frame or tibble

`...` A dplyr::filter expression. Used to select subgroup.

Value

A character string

Examples

```

library(dplyr)
library(freqtables)

data(mtcars)

# Get sample size for cars with 4 cylinders
mtcars %>% get_group_n(cyl == 4)

#> [1] "N = 11"

```

Index

* **datasets**

freq_study, [3](#)

freq_format, [2](#)

freq_study, [3](#)

freq_table, [4](#)

freq_test, [7](#)

get_group_n, [9](#)